

NC6000 Series TECHNICAL INFORMATION

| SIZE AND WEIGHT | NC6000 | NC6000B | NC6000xp | NC6030 |
|-------------------------------|---|------------------------------|------------------------------|------------------------------|
| Weight: | 10.5Kg | 14.9Kg | 6.60Kg | 4.5Kg |
| Size: | 500mmW, 185mmH, 390mmD | 500mmW, 185mmH, 390mmD | 410mmW, 170mmH, 320mmD | 270mmW, 174mmH, 248mmD |
| CONNECTIONS: | | | | |
| Power: | IEC (5A fuse lead) | IEC (5A fuse lead) | IEC (5A fuse lead) | IEC (5A fuse lead) |
| USB | 6xUSB | 6xUSB | 1xUSB | 1xUSB |
| Serial | 2xSerial ports | 2xSerial ports | N/A | 2xSerial ports |
| Cradles | 8xSepura Cradles | 8xSepura Cradles | 8xSepura Cradles | 2xSepura Cradles |
| Ethernet: | RJ45 | RJ45 | N/A | N/A |
| PC SPECIFICATION: | | | | |
| PC: | 2GHz Processor & 2GB Memory. Suitable for running radio manager. | | N/A | N/A |
| OPERATING TEMPERATURE: | | | | |
| Temperature range: | 0°C to 40°C | 0°C to 40°C | 0°C to 40°C | N/A |
| POWER REQUIREMENTS: | | | | |
| Input range: | 115-230V AC, 50/60Hz | 115-230V AC, 50/60Hz | 100-240V AC, 50/60Hz | N/A |
| COMPATIBILITY: | | | | |
| Compatible with: | Sepura: SRC Sepura: SRH 2000, 3000, 2500, 3900, 3300. Sepura: STP8000 | | | |
| | | | | |