

# NC6050 Series TECHNICAL INFORMATION

<b>SIZE AND WEIGHT:</b>	<b>NC6054 STP/SRH</b>	<b>NC6050 STP/SRH</b>
Wall Mount:	Weight: approx. 5kg 390mmW, 200mmH, 160mmD	Weight: approx. 2kg 125mmW, 200mmH, 145mmD
Desk Mount:	Weight: approx. 5kg 390mmW, 130mmH, 200mmD  (Dimensions and weight excluding radio)	Weight: approx. 2kg 125mmW, 130mmH, 200mmD  (Dimensions and weight excluding radio)
<b>POWER REQUIREMENTS:</b>		
Input range:	100-240V AC, 47-63Hz	85-264V AC, 47-440Hz
<b>CONNECTIONS:</b>		
Power:	Fused IEC (3.15A Fuse)	
Ethernet port: Protection:	10/100Mbps (RJ45) Built in 1.5KV magnetic isolation	
<b>OPERATING TEMPERATURE:</b>		
Temperature range:	0-55°C (32-131°F)	
<b>SERIAL COMMUNICATION PARAMETERS:</b>		
Parity Data bits Stop bits Flow control Transmission speed Bandwidth requirements	None, Even, Odd, Space, Mark 5, 6, 7, 8 1, 1.5, 2 RTS/CTS, DSR/DTR (for RS-232 only), XON/XOFF 50 bps to 921.6 Kbps (110 bps to 230.4 Kbps for NC6050) 50Kbytes when programing at 115200 baud rate	
Requires a static IP address		
<b>Options</b>		
Radio charging		